

PARTALL Film #10

Safety Data Sheet
according to OSHA HCS and GHS - Canada WHMIS 2015

Version: 4.1
Revision date: 2019-05-10
Print date: 2019-06-17

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product Identifier**

Product form : Mixture
Trade name : PARTALL Film #10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Release agent

1.3 Details of the supplier of the safety data sheet

Company : REXCO
P.O. Box 80996
Conyers, GA 30013
U.S.A.

Telephone : 1-770-483-7610
Fax : 1-770-483-8550
Email : info@rexco-usa.com
Website : www.rexco-usa.com

1.4 Emergency telephone number

Chemtrec (24 hours/day) : 1-800-434-9300 (USA and Canada)
: 1-703-527-3887 (international; collect calls accepted)

SECTION 2. Hazards Identification**2.1 Classification of the substance or mixture**

Classification according to OSHA-HCS and GHS-Canada WHMIS 2015

Flam. Liq. 3	H226	Flammable liquid and vapour
Acute Tox. 4	H302	Harmful if swallowed
Skin Irrit. 2	H315	Causes skin irritation
Eye Dam. 1	H318	Causes serious eye damage
STOT SE 3	H335	May cause respiratory irritation
STOT SE 3	H336	May cause drowsiness or dizziness

See section 16 for full text of H-phrases.

2.2 Label elements

Labeling according to the Globally Harmonized System (GHS)

Pictograms



Signal word : **Danger**

Hazard statements

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation

H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: See Section 5.2 for extinguishing media.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3. Composition/information on ingredients**3.1 Substances**

Not applicable. This material is not defined as a substance.

3.2 Mixtures

This material is defined as a mixture.

Components contributing to the classification of this material

	%
Ethanol	20 - 25
CAS No. 64-17-5	
EC No. 200-578-6	
Flam. Liq. 2, H225	
Eye Irrit. 2, H319	
STOT SE 3, H335	
STOT SE 3, H336	
Isopropyl alcohol	2 - 6

CAS No. 67-63-0
EC No. 200-661-7
Flam. Liq. 2, H225
Eye Irrit. 2, H319
STOT SE 3, H336

n-Butanol
CAS No. 71-36-3
EC No. 200-751-6
Flam. Liq. 3, H226
Acute Tox. 4, H302
Skin Irrit. 2, H315
Eye Dam. 1, H318
STOT SE 3, H335
STOT SE 3, H336

1 - 3

Components not listed are either non-hazardous or are below reportable limits. Concentrations are in percent by weight.

SECTION 4. First aid measures

General information

Do not leave victim unattended. Show this safety data sheet to doctor in attendance.

4.1 Description of first aid measures

Inhalation

Provide fresh air if light-headed or having difficulty breathing. Provide artificial respiration if needed. If difficulty breathing persists, seek medical attention. If unconscious, place victim on their side for transport to medical facility.

Skin

Remove contaminated clothing and wash affected area with soap and warm water. If irritation persists, seek medical attention. Launder contaminated clothing and shoes prior to reuse.

Eyes

Flush immediately with cold water for 15 minutes. Remove contact lenses. Keep eye wide open while rinsing. Get prompt medical attention.

Ingestion

Seek immediate medical attention. Do not induce vomiting. If spontaneous vomiting occurs keep victim's head below hips to prevent aspiration into lungs. Do not leave individual unattended.

4.2 Most important symptoms and effects, both acute and delayed

Can cause eye irritation. May cause skin irritation. If swallowed, may cause nausea, vomiting, gastrointestinal bleeding, abdominal pain, and central nervous system depression with symptoms such as drunkenness, unconsciousness, narcosis, coma, respiratory failure, and death. Prolonged or repeated exposure may result in conjunctiva, skin dermatitis, irritation of mucous membranes, liver damage, and central nervous system depression, including headache, dizziness, loss of coordination, and unconsciousness.

4.3 Indication of any immediate medical attention and special treatment

Treat symptomatically. Seek immediate medical attention if ingested.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Standard procedure for chemical fires. Use dry chemicals, carbon dioxide, water fog, water spray, or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Water may be unsuitable as an extinguishing media but helpful in keeping adjacent areas cool. Avoid spreading burning liquid with water used for cooling purposes. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

None inherent to this product.

Hazardous decomposition products formed during combustion

Carbon oxides, aldehydes, acids

5.3 Advice for firefighters

Evacuate area. Firefighters should use standard protective equipment and should use self-contained breathing apparatus in enclosed spaces. Use water spray to cool surfaces exposed to fire and to protect personnel.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Ensure adequate ventilation. Keep sources of ignition and hot metal surfaces isolated from spill.

6.2 Environmental precautions

Prevent product from entering drains, waterways, sewers, and soil. Stop spill at source and prevent further leakage or spillage if safe to do so. Notify proper authorities if product enters sewers or public waters.

6.3 Methods and material for containment and cleaning up

Flush spilled material into suitable retaining areas or containers. Small amounts of spilled material may be absorbed with standard absorbent such as sand, vermiculite, or diatomaceous earth. Confine spill and place into suitable closed container for disposal. Dispose of in accordance with regional, national, and local laws and regulations.

6.4 Reference to other sections

Section 7: safe handling. Section 8: personal and protective equipment. Section 10: incompatible materials. Section 13: disposal information. Section 16: full text of abbreviations.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Use in a well ventilated area or use appropriate respirator when ventilation is inadequate. Do not breathe vapor. Wear personal protective clothing and equipment as indicated in Section 8. Eliminate all sources of ignition. Use explosion-proof equipment. Do not ingest. Use good industrial hygiene practices in handling this material. Do not smoke, eat or drink while using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and leaving work. Clean up spills as soon as they occur. Empty containers may contain residual amounts of this product and should be handled with care. Do not reuse containers.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area away from direct sunlight. Avoid freezing. Store away from incompatible materials (see Section 10) and food and drink. Store in original container. Keep container tightly closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Provide appropriate fire extinguishers and spill cleanup equipment in or near storage area. Keep unauthorized personnel away.

7.3 Specific end uses

See section 1.2

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring:

Ethanol

CAS No. 64-17-5

EC No. 200-578-6

LTEL - 8 hours	STEL - 15 minutes
----------------	-------------------

	ppm	mg/m ³	ppm	mg/m ³
Australia	1000	1880		
Austria	1000	1900	2000	3800
Belgium	1000	1907		
Canada - Ontario			1000	
Canada - Québec	1000	1880		
Denmark	1000	1900	2000	3800
Finland	1000	1900	1300	2500
France	1000	1900	5000	9500
Germany (AGS)	500	960	1000	1920
Germany (DFG)	200	380	800	1520
Hungary		1900		7600
Ireland			1000	
Latvia		1000		
New Zealand	1000	1880		
Poland		1900		
Romania	1000	1900	5000	9500
Singapore	1000	1880		
South Korea	1000	1900		
Spain			1000	1910
Sweden	500	1000	1000	1900
Switzerland	500	960	1000	1920
The Netherlands		260		1900
USA (NIOSH)	1000	1900		
USA (OSHA)	1000	1900		
United Kingdom	1000	1920		

Isopropyl alcohol

CAS No. 67-63-0

EC No. 200-661-7

	LTEL - 8 hours		STEL - 15 minutes	
	ppm	mg/m ³	ppm	mg/m ³
Australia	400	983	500	1230
Austria	200	500	800	2000
Belgium	200	500	400	1000
Canada - Ontario	200		400	
Canada - Québec	400	983	500	1230
Denmark	200	490	400	980
Finland	200	500	250	620
France	--	--	400	980
Germany (AGS)	200	500	400	1000
Germany (DFG)	200	500	400	1000
Hungary		500		2000
Ireland	200		400	
Japan	400			
Japan (JSOH)	400	980		
Latvia		350		600
New Zealand	400	983	500	1230
People's Republic of China		350		700
Poland		900		1200
Romania	70	600	93	800
Singapore	400	983	500	1230
South Korea	200	480	400	980
Spain	200	500	400	1000
Sweden	150	350	250	600
Switzerland	200	500	400	1000
USA (NIOSH)	400	980	500	1225
USA (OSHA)	400	980		
United Kingdom	400	999	500	1250

n-Butanol
CAS No. 71-36-3
EC No. 200-751-6

	LTEL - 8 hours		STEL - 15 minutes	
	ppm	mg/m ³	ppm	mg/m ³
Australia			50	152
Austria	50	150	200	600
Belgium	20	62		
Canada - Ontario	20			
Canada - Québec			50	152
Denmark	50	150	50	150
Finland	50	150	75	230
France			50	150
Germany (AGS)	100	310	100	310
Germany (DFG)	100	310	100	310
Hungary		45		90
Ireland	20			
Japan	25			
Japan (JSOH)	50	150		
Latvia		10		
New Zealand			50	150
People's Republic of China		100		
Poland		50		150
Romania	33	100	66	200
Singapore			50	152
South Korea	20	60		
Spain	20	61	50	154
Sweden	15	45	30	90
Switzerland	100	310	100	310
USA (NIOSH)			50	150
USA (OSHA)	100	300		
United Kingdom			50	154

Ingredients with biological monitoring guidance values (BMGV) and/or biological exposure index (BEI):

Isopropyl alcohol
CAS No. 67-63-0
EC No. 200-661-7
BMGV: 40 mg acetone/L urine (end of shift at end of workweek)

8.2 Exposure controls

Engineering controls

Provide adequate local exhaust ventilation. Use explosion-proof electrical/ventilating/lighting equipment. Maintain eye wash fountain and safety shower in work area.

Personal protective equipment

General protective and hygienic measures

Do not eat, drink, or smoke while using. Wash hands before breaks and at the end of workday. Immediately remove all soiled or contaminated clothing.

Eye and face protection

Chemical safety glasses with side shields, goggles or face shield are recommended. Eye wash stations are recommended for the work area.

Skin and body protection

Wear chemical resistant clothing and shoes. Safety showers are recommended for the work area.

Respiratory protection

Provide sufficient general and/or local exhaust. If engineering controls are not sufficient to protect worker health use a half-face filter respirator approved under applicable regulatory standards.

Hand protection

Wear chemical resistant impervious gloves. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves.

Environmental controls

Prevent product from entering drains. Stop spill at source and prevent further leakage or spillage if safe to do so. If product contaminates rivers and lakes or drains, notify proper authorities.

SECTION 9. Physical and chemical properties

Physical state	: Liquid
Physical form	: Liquid
Colour	: Green or Clear
Odour	: Alcohol
Odour threshold	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Initial boiling point and boiling range	: 70 °C – 104 °C (158 °F – 220 °F)
Flammability	: Flammable liquid
Upper flammability limit	: 0.187
Lower flammability limit	: 0.033
Flash point	: 24 °C (76 °F)
Auto-ignition temperature	: 354 °C (670 °F)
Decomposition temperature	: 354 °C (670 °F)
pH	: 5.0 - 6.9
Viscosity	: 25 - 70 cP
Solubility (water)	: Fully soluble
Partition coefficient n-octanol/water (log value)	: No data available
Vapour pressure	: No data available
Relative density at 24 °C (water = 1)	: 0.94 - 0.98
Volatile organic compounds (VOC)	
VOC - actual	: 289 g/L
VOC less water & exempt solvents	: 730 g/L

SECTION 10. Stability and reactivity

10.1 Reactivity

Not reactive under normal conditions of use.

10.2 Chemical stability

Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid

Avoid heat, sparks, open flames, hot surfaces, or other sources of ignition.

10.5 Incompatible materials

Strong oxidizing agents, acids, alkali materials

10.6 Hazardous decomposition products

Carbon oxides, aldehydes, acids

SECTION 11. Toxicological Information

11.1 Information on toxicological effects

Acute toxicity : Not classified

LD/LC50 values that are relevant for classification:

Ethanol

CAS No. 64-17-5

EC No. 200-578-6

Oral	LD50	rat	10740 mg/kg
Dermal	LD50	rabbit	> 16000 mg/kg

Isopropyl alcohol

CAS No. 67-63-0

EC No. 200-661-7

Oral	LD50	rat	5045 mg/kg
Dermal	LD50	rabbit	12870 mg/kg
Inhalative	LC50	rat	73 mg/l/4h

n-Butanol

CAS No. 71-36-3

EC No. 200-751-6

Oral	LD50	rat	790 mg/kg
Dermal	LD50	rabbit	3400 mg/kg
Inhalative	LC50	rat	24 mg/l/4h
Inhalative	LC50	rat	8000 ppm/4h

Skin corrosion/irritation : Expected to be slightly irritating
 Serious eye damage/irritation : Expected to be slightly irritating
 Respiratory or skin sensitisation : Not classified
 Germ cell mutagenicity : Not classified
 Carcinogenicity : Not classified
 Reproductive toxicity : Not classified
 STOT-single exposure : Not classified
 STOT-repeated exposure : Not classified
 Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1 Toxicity : Not expected to be toxic.
12.2 Persistence and degradability : Expected to be inherently biodegradable.
12.3 Bioaccumulative potential : No data available
12.4 Mobility in soil : No data available
12.5 Other adverse effects : No data available
12.6 General notes : No data available

SECTION 13. Disposal considerations**13.1 Waste treatment methods**

Dispose of in accordance with regional, national, and local laws and regulations.

Material disposal : Do not dispose of waste into sewer. Do not contaminate ponds, waterways, or ditches with product or used container. Send to a licensed waste management company.

Container disposal : Do not dispose of waste into sewer. Do not contaminate ponds, waterways, or ditches with product or used container. Send to a licensed waste management company.

SECTION 14. Transport information

14.1 UN number

UN1987

14.2 UN proper shipping name

DOT : ALCOHOLS, N.O.S.

ADR : ALCOHOLS, N.O.S.

IMDG : ALCOHOLS, N.O.S. (ethyl alcohol)

IATA : ALCOHOLS, N.O.S. (ethyl alcohol)

14.3 Transport hazard class

3

14.4 Packing group

III

14.5 Environmental hazards

No

14.6 Special precautions for user

EmS: F-E, S-D

Stowage category: A

Kemler code: 30

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

14.8 Additional information

Limited Quantity: 5 L

Limited Quantity: 5 L

Tunnel code: D/E

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No information available for this material. Information provided is for components.

OSHA Hazard Communication Standard

This material is hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200

Superfund Amendments and Reauthorization Act (SARA)

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazard Categories

Fire hazard, immediate (acute) health hazard, delayed (chronic) health hazard

SARA 313 Components

Isopropyl Alcohol (CAS No. 67-63-0); n-Butanol (CAS No. 71-36-3)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

n-Butanol (CAS No. 71-36-3); Reportable Quantity (RQ) = 5000 pounds

California Proposition 65

No chemicals in this material are subject to the reporting requirements of California Proposition 65.

This product contains the following Right to Know components:

Component

Ethanol (CAS No. 64-17-5)
Isopropyl Alcohol (CAS No. 67-63-0)
n-Butanol (CAS No. 71-36-3)

U.S. State Right to Know list

: Massachusetts, New Jersey, Pennsylvania
: Massachusetts, New Jersey, Pennsylvania
: Massachusetts, New Jersey, Pennsylvania

Regulation (EC) No 1907/2006, Title VII, Article 57 - Substances of Very High Concern (SVHC)

No components of this material are listed.

Regulation (EC) No 1907/2006, Annex XIV - List of Substances Subject to Authorization

No components of this material are listed.

Regulation (EC) No 1907/2006, Annex XVII - Restrictions of Certain Dangerous Substances, Mixtures and Articles

Conditions of restriction: 3

International Agency for Research on Cancer (IARC)

This product contains the following chemicals classified by IARC as carcinogenic:

Isopropyl alcohol
CAS No. 67-63-0
EC No. 200-661-7
Group 3

Chemical inventories

Components are listed or exempted from listing on the following chemical inventories:

AICS	Australian Inventory of Chemical Substances
DSL / NDSL	Domestic Substances List / Non-Domestic Substances List
EINECS	European Inventory of Existing Commercial Chemical Substances
ENCS	Existing and New Chemical Substances
IECS	Inventory of Existing Chemical Substances Produced or Imported in China
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substances Control Act

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

SECTION 16. Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. REXCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Abbreviations and acronyms

Acute Tox. 4	Acute toxicity - Category 4
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AGS	Committee on Hazardous Substances
CAS	Chemical Abstract Service
DFG	German Research Foundation
DOT	U.S. Department of Transportation
EC	European Community
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
Eye Dam. 1	Eye damage - Category 1

Flam. Liq. 3	Flammable liquids - Category 3
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
JSOH	Japanese Society for Oral Health
LC50	Lethal concentration, 50 percent
LD50	Lethal does, 50 percent
LTEL	Long term exposure limit
NIOSH	National Institute for Occupational Safety and Health
OSHA	U.S. Occupational Safety and Health Administration
OSHA HCS	U.S. Occupational Safety and Health Administration Hazard Communication Standard
PBT	Persistent, Bioaccumulative and Toxic
Skin Irrit. 2	Skin corrosion/irritation - Category 2
STEL	Short term exposure limit
STOT SE 3	Specific target organ toxicity (single exposure) - Category 3
vPvB	very Persistent and very Bioaccumulative