

FORMULA FIVE Glossy Top Coat

Safety Data Sheet
according to OSHA HCS and GHS - Canada WHMIS 2015

Version: 5.0
Revision date: 2021-01-01
Print date: 2021-02-03

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Product Identifier**

Product form : Mixture
Trade name : FORMULA FIVE Glossy Top Coat

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Release agent

1.3 Details of the supplier of the safety data sheet

Supplier : REXCO
P.O. Box 80996
Conyers, GA 30013
U.S.A.

Telephone : 1-770-483-7610
Fax : 1-770-483-8550
Email : info@rexco-usa.com
Website : www.rexco-usa.com

1.4 Emergency telephone number

Chemtrec (24 hours/day) : 1-800-434-9300 (USA and Canada)
: 1-703-527-3887 (international; collect calls accepted)

SECTION 2. Hazards Identification**2.1 Classification of the substance or mixture**

Classification according to OSHA-HCS and GHS-Canada WHMIS 2015

| | | |
|-------------------|------|---|
| Flam. Liq. 2 | H225 | Highly flammable liquid and vapour |
| Asp. Tox. 1 | H304 | May be fatal if swallowed and enters airways |
| Skin Irrit. 2 | H315 | Causes skin irritation |
| STOT SE 3 | H336 | May cause drowsiness or dizziness |
| Aquatic Chronic 2 | H411 | Toxic to aquatic life with long lasting effects |

See section 16 for full text of H-phrases.

2.2 Label elements

Labeling according to the Globally Harmonized System (GHS)

Pictograms



Signal word : **Danger**

Hazard statements

| | |
|------|--|
| H225 | Highly flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H336 | May cause drowsiness or dizziness |

H411 Toxic to aquatic life with long lasting effects

Precautionary statements

| | |
|--------------------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read label before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground and bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P242 | Use non-sparking tools. |
| P243 | Take action to prevent static discharges. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/doctor. |
| P302 + P352 | IF ON SKIN: Wash with plenty of water. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P312 | Call a POISON CENTER/doctor if you feel unwell. |
| P321 | Specific treatment (see on this label). |
| P331 | Do NOT induce vomiting. |
| P332 + P313 | If skin irritation occurs: Get medical advice/attention. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P370 + P378 | In case of fire: See Section 5.2 for extinguishing media. |
| P391 | Collect spillage. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |

2.3 Other hazards

Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3. Composition/information on ingredients

3.1 Substances

Not applicable. This material is not defined as a substance.

3.2 Mixtures

This material is defined as a mixture.

Components contributing to the classification of this material

| | % |
|-------------------------------------|---------|
| Naphtha (petroleum), light alkylate | 50 - 75 |
| CAS No. 64741-66-8 | |
| Flam. Liq. 2, H225 | |
| Asp. Tox. 1, H304 | |
| Skin Irrit. 2, H315 | |
| STOT SE 3, H336 | |
| Aquatic Chronic 2, H411 | |
| Heptane | 20 - 25 |
| CAS No. 142-82-5 | |
| Flam. Liq. 2, H225 | |
| Asp. Tox. 1, H304 | |
| Skin Irrit. 2, H315 | |
| STOT SE 3, H336 | |

Aquatic Acute 1
Aquatic Chronic 1

Naphtha (petroleum), hydrotreated heavy 10 - 25
CAS No. 64742-48-9
Flam. Liq. 3, H226
Asp. Tox. 1, H304
Aquatic Chronic 4, H413

Trade secret 0.1 - 2.5
CAS No. --
Acute Tox. 4 , H302

Trade secret 0.1 - 2.5
CAS No. --
EC No. --

2,2,4-trimethylpentane 0.01 - 0.25
CAS No. 540-84-1
Flam. Liq. 2, H225
Asp. Tox. 1, H304
Skin Irrit. 2, H315
STOT SE 3, H336
Aquatic Acute 1
Aquatic Chronic 1

Components not listed are either non-hazardous or are below reportable limits. Concentrations are in percent by weight.

SECTION 4. First aid measures

General information

Do not leave victim unattended. Show this safety data sheet to doctor in attendance.

4.1 Description of first aid measures

Inhalation

Provide fresh air if light-headed or having difficulty breathing. Provide artificial respiration if needed. If difficulty breathing persists, seek medical attention. If unconscious, place victim on their side for transport to medical facility.

Skin

Remove contaminated clothing and wash affected area with soap and warm water. If irritation persists, seek medical attention. Launder contaminated clothing and shoes prior to reuse.

Eyes

Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open when rinsing. If eye irritation persists, consult a specialist.

Ingestion

Seek immediate medical attention. Do not induce vomiting. If spontaneous vomiting occurs keep victim's head below hips to prevent aspiration into lungs. Do not leave individual unattended.

4.2 Most important symptoms and effects, both acute and delayed

No data available

4.3 Indication of any immediate medical attention and special treatment

Treat symptomatically. Seek immediate medical attention if ingested.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Standard procedure for chemical fires. Use dry chemicals, carbon dioxide, water fog, water spray, or alcohol-resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Water may be unsuitable as an extinguishing media but helpful in keeping adjacent areas cool. Avoid spreading burning liquid with water used for cooling purposes. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

None inherent to this product.

Hazardous decomposition products formed during combustion

Carbon oxides, hydrocarbons, aldehydes

5.3 Advice for firefighters

Evacuate area. Firefighters should use standard protective equipment and should use self-contained breathing apparatus in enclosed spaces. Use water spray to cool surfaces exposed to fire and to protect personnel.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Ensure adequate ventilation. Keep sources of ignition and hot metal surfaces isolated from spill.

6.2 Environmental precautions

Prevent product from entering drains, waterways, sewers, and soil. Stop spill at source and prevent further leakage or spillage if safe to do so. Notify proper authorities if product enters sewers or public waters.

6.3 Methods and material for containment and cleaning up

Flush spilled material into suitable retaining areas or containers. Small amounts of spilled material may be absorbed with standard absorbent such as sand, vermiculite, or diatomaceous earth. Confine spill and place into suitable closed container for disposal. Dispose of in accordance with regional, national, and local laws and regulations.

6.4 Reference to other sections

Section 7: safe handling. Section 8: personal and protective equipment. Section 10: incompatible materials. Section 13: disposal information. Section 16: full text of abbreviations.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Use in a well ventilated area or use appropriate respirator when ventilation is inadequate. Do not breathe vapor. Wear personal protective clothing and equipment as indicated in Section 8. Eliminate all sources of ignition. Use explosion-proof equipment. Do not ingest. Use good industrial hygiene practices in handling this material. Do not smoke, eat or drink while using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and leaving work. Clean up spills as soon as they occur. Empty containers may contain residual amounts of this product and should be handled with care. Do not reuse containers.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area away from direct sunlight. Avoid freezing. Store away from incompatible materials (see Section 10) and food and drink. Store in original container. Keep container tightly closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Provide appropriate fire extinguishers and spill cleanup equipment in or near storage area. Keep unauthorized personnel away.

7.3 Specific end uses

See section 1.2

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring:

Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9

| | LTEL - 8 hours | | STEL - 15 minutes | |
|---------------|----------------|-------------------|-------------------|-------------------|
| | ppm | mg/m ³ | ppm | mg/m ³ |
| Germany (DFG) | 50 | 300 | 100 | 600 |
| Poland | | 300 | | 900 |
| Switzerland | 50 | 300 | 100 | 600 |

Heptane

CAS No. 142-82-5

| | LTEL - 8 hours | | STEL - 15 minutes | |
|----------------------------|----------------|-------------------|-------------------|-------------------|
| | ppm | mg/m ³ | ppm | mg/m ³ |
| Australia | 400 | 1640 | 500 | 2050 |
| Austria | 500 | 2000 | 2000 | 8000 |
| Belgium | 400 | 1664 | 500 | 2085 |
| Canada - Ontario | 400 | | 500 | |
| Canada - Québec | 400 | 1640 | 500 | 2050 |
| Denmark | 200 | 820 | 400 | 1640 |
| Finland | 300 | 1200 | 500 | 2100 |
| France | 400 | 1668 | 500 | 2085 |
| Germany (AGS) | 500 | 2100 | 500 | 2100 |
| Germany (DFG) | 500 | 2100 | 500 | 2100 |
| Hungary | | 2000 | | 8000 |
| Ireland | 500 | 2085 | | |
| Italy | 500 | 2085 | | |
| Japan (JSOH) | 200 | 820 | | |
| Latvia | 85 | 350 | 500 | 2085 |
| New Zealand | 400 | 1640 | 500 | 2050 |
| People's Republic of China | | 500 | | 1000 |
| Romania | 500 | 2085 | | |
| South Korea | 400 | 1600 | 500 | 2000 |
| Sweden | 200 | 800 | 300 | 1200 |
| Switzerland | 400 | 1600 | 400 | 1600 |
| The Netherlands | | 1200 | | 1600 |
| Turkey | 500 | 2085 | | |
| USA (ACGIH) | 400 | 1640 | 500 | 2050 |
| USA (NIOSH) | 85 | 350 | 440 | 1800 |
| USA (OSHA) | 500 | 2000 | | |
| United Kingdom | 500 | | | |

Ingredients with biological monitoring guidance values (BMGV) and/or biological exposure index (BEI):

Contains no substances with biological monitoring guidance values.

8.2 Exposure controls**Engineering controls**

Provide adequate local exhaust ventilation. Use explosion-proof electrical/ventilating/lighting equipment. Maintain eye wash fountain and safety shower in work area.

Personal protective equipment**General protective and hygienic measures**

Do not eat, drink, or smoke while using. Wash hands before breaks and at the end of workday. Immediately remove all soiled or contaminated clothing.

Eye and face protection

Chemical safety glasses with side shields, goggles or face shield are recommended. Eye wash stations are recommended for the work area.

Skin and body protection

Wear chemical resistant clothing and shoes. Safety showers are recommended for the work area.

Respiratory protection

Provide sufficient general and/or local exhaust. If engineering controls are not sufficient to protect worker health use a respirator approved under applicable regulatory standards.

Hand protection

Wear chemical resistant impervious gloves. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves.

Environmental controls

Prevent product from entering drains. Stop spill at source and prevent further leakage or spillage if safe to do so. If product contaminates rivers and lakes or drains, notify proper authorities.

SECTION 9. Physical and chemical properties

| | |
|--|---------------------|
| Physical state | : Liquid |
| Physical form | : Liquid |
| Colour | : Clear |
| Odour | : Characteristic |
| Odour threshold | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Initial boiling point and boiling range | : No data available |
| Flammability | : Flammable liquid |
| Upper flammability limit | : No data available |
| Lower flammability limit | : No data available |
| Flash point | : 0 °C (32 °F) |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| pH | : No data available |
| Viscosity | : < 15 cP |
| Solubility (water) | : Not soluble |
| Partition coefficient n-octanol/water (log value) | : No data available |
| Vapour pressure | : No data available |
| Relative density at 20 °C (water = 1) | : 0.71 - 0.75 |
| Volatile organic compounds (VOC) | |
| VOC - actual | : 729 g/L |
| VOC less water & exempt solvents | : 729 g/L |

SECTION 10. Stability and reactivity**10.1 Reactivity**

Not reactive under normal conditions of use.

10.2 Chemical stability

Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid

Avoid heat, sparks, open flames, hot surfaces, or other sources of ignition.

10.5 Incompatible materials

Oxidizing agents, acids, bases, strong reducing agents

10.6 Hazardous decomposition products

Carbon oxides, hydrocarbons, aldehydes

SECTION 11. Toxicological Information**Acute toxicity** : Not classified

LD/LC50 values that are relevant for classification:

Naphtha (petroleum), light alkylate
CAS No. 64741-66-8

| | | | |
|------------|------|--------|--------------|
| Oral | LD50 | rat | > 5000 mg/kg |
| Dermal | LD50 | rabbit | > 2000 mg/kg |
| Inhalative | LC50 | rat | 22 mg/l/4h |

Naphtha (petroleum), hydrotreated heavy
CAS No. 64742-48-9

| | | | |
|--------|------|--------|--------------|
| Oral | LD50 | rat | > 5000 mg/kg |
| Dermal | LD50 | rabbit | > 5000 mg/kg |

Skin corrosion/irritation : Causes skin irritation.
 Serious eye damage/irritation : Not classified
 Respiratory or skin sensitisation : Not classified
 Germ cell mutagenicity : Not classified
 Carcinogenicity : Not classified
 Reproductive toxicity : Not classified
 STOT-single exposure : May cause drowsiness or dizziness.
 STOT-repeated exposure : Not classified
 Aspiration hazard : May be fatal if swallowed and enters airway

SECTION 12: Ecological information

12.1 Toxicity : Aquatic toxicity:
 Naphtha (petroleum), light alkylate
 CAS No. 64741-66-8
 LL50 | 18.4 mg/l (Oncorhynchus mykiss (rainbow trout))

12.2 Persistence and degradability : No data available
12.3 Bioaccumulative potential : No data available
12.4 Mobility in soil : No data available
12.5 Other adverse effects : Hazardous for water. Dangerous to drinking water even in small quantities. Toxic to fish and aquatic organisms.
12.6 General notes : No data available

SECTION 13. Disposal considerations**13.1 Waste treatment methods**

Dispose of in accordance with regional, national, and local laws and regulations.

Material disposal : Do not dispose of waste into sewer. Do not contaminate ponds, waterways, or ditches with product or used container. Send to a licensed waste management company.

Container disposal : Do not dispose of waste into sewer. Do not contaminate ponds, waterways, or ditches with product or used container. Send to a licensed waste management company.

SECTION 14. Transport information**14.1 UN number**

UN1866

14.2 UN proper shipping name

DOT : RESIN SOLUTION
ADR : RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS
IMDG : RESIN SOLUTION (naphtha (petroleum), hydrotreated heavy), MARINE POLLUTANT
IATA : RESIN SOLUTION

14.3 Transport hazard class

3

14.4 Packing group

II

14.5 Environmental hazards

MARINE POLLUTANT

14.6 Special precautions for user

EmS: F-E, S-E
Stowage category: B
Kemler code: 33

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

14.8 Additional information

Limited Quantity: 5.0 L
Limited Quantity: 5.0 L
Tunnel code: D/E

SECTION 15. Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No information available for this material. Information provided is for components.

OSHA Hazard Communication Standard

This material is hazardous in accordance with OSHA HazCom 2012, 29 CFR 1910.1200

Superfund Amendments and Reauthorization Act (SARA)**SARA 302 Components**

No data available

SARA 311/312 Hazard Categories

No information available for this material. Information provided is for components.

SARA 313 Components

All components are listed.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

No chemicals in this material are subject to the reporting requirements of CERCLA.

California Proposition 65

WARNING: This product can expose you to chemicals including toluene, which is known to the State of California to cause birth defects and other reproductive harm. For more information go to www.P65Warnings.ca.gov.

This product contains the following Right to Know components:

Component
Heptane (CAS No. 142-82-5)

U.S. State Right to Know list
: Massachusetts, New Jersey, Pennsylvania

2,2,4-trimethylpentane (CAS No. 5404-84-1)

: Massachusetts, New Jersey, Pennsylvania

International Agency for Research on Cancer (IARC)

This product contains the following chemicals classified by IARC as carcinogenic:

Toluene

CAS No. 108-88-3

Group 3

Chemical inventories

Components are listed or exempted from listing on the following chemical inventories:

| | |
|------------|---|
| AICS | Australian Inventory of Chemical Substances |
| DSL / NDSL | Domestic Substances List / Non-Domestic Substances List |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ENCS | Existing and New Chemical Substances |
| IECS | Inventory of Existing Chemical Substances Produced or Imported in China |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substances Control Act |

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this product.

SECTION 16. Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. REXCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Abbreviations and acronyms

| | |
|-------------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| AGS | Committee on Hazardous Substances |
| Aquatic Acute 1 | Acute aquatic toxicity - Category 1 |
| Aquatic Chronic 1 | Chronic aquatic toxicity - Category 1 |
| Aquatic Chronic 2 | Chronic aquatic toxicity - Category 2 |
| Aquatic Chronic 4 | Chronic aquatic toxicity - Category 4 |
| Asp. Tox. 1 | Aspiration hazard - Category 1 |
| CAS | Chemical Abstract Service |
| DFG | German Research Foundation |
| DOT | U.S. Department of Transportation |
| EmS | Emergency Response Procedures for Ships Carrying Dangerous Goods |
| Flam. Liq. 2 | Flammable liquids - Category 2 |
| Flam. Liq. 3 | Flammable liquids - Category 3 |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| JSOH | Japanese Society for Oral Health |
| LC50 | Lethal concentration, 50 percent |
| LD50 | Lethal dose, 50 percent |
| LTEL | Long term exposure limit |
| NIOSH | National Institute for Occupational Safety and Health |
| OSHA | U.S. Occupational Safety and Health Administration |
| OSHA HCS | U.S. Occupational Safety and Health Administration Hazard Communication Standard |
| PBT | Persistent, Bioaccumulative and Toxic |
| Skin Irrit. 2 | Skin corrosion/irritation - Category 2 |

| | |
|-----------|---|
| STEL | Short term exposure limit |
| STOT SE 3 | Specific target organ toxicity (single exposure) - Category 3 |
| vPvB | very Persistent and very Bioaccumulative |